

MATERIAL SAFETY DATA SHEET

Blaze Products

JELLED ETHANOL (CONSUMER COMMODITY)

BLAZE JELLED ETHANOL CHAFING DISH FUEL FOR 8 OZ. AND 2 5/8 OZ.

BLAZE MSDS NUMBER: BB100
EFFECTIVE DATE: MAY 31, 2001
Blaze Products Corporation

P. O. Box 339
Shelbyville, Kentucky 40066-0339
Telephone: (502) 633-0650

Twenty Four (24) Hour Emergency Assistance:
CHEMTREC 1-800-424-9300 day or night.
Outside the continental United States, call CHEMTREC at 1-703-527-3887 (collect calls accepted).

Blaze Products Corporation urges the customer receiving this Material Safety Data Sheet (MSDS) to study it carefully to become aware of hazards, if any, of the product involved. In the interest of safety, you should: (1) notify your employees, agents, and contractors of the information on this sheet, and (2) furnish a copy to each of your customers to inform their employees and customers as well.

SECTION I ? PRODUCT INFORMATION

TRADE NAME: B-B100, B-B400, B-B500, B-B600, B-B800
PACKAGES: 8 ounce cans (72, 48, 12 units/case), and 2 5/8 ounce cans (144 units/case)

SYNONYMS: Jelled Ethanol (Consumer Commodity)
PRODUCT IS:

Mixture; CAS Number not applicable: X
Chemical Substance:

CHEMICAL FAMILY: Not applicable
GENERAL INFORMATION: A jelled alcohol fuel for warming food. The fuel is jelled Ethanol.

Section II ? HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Table with 4 columns: COMPOSITION, CAS RN., %, TLV (Units). Rows include Ethanol, Methanol, Acetone, and Denatonium Benzoate.

SECTION III ? PHYSICAL/CHEMICAL CHARACTERISTICS

APPEARANCE AND ODOR: Pink-red jell with alcohol odor.
SPECIFIC GRAVITY: Not applicable
% VOLATILE BY VOLUME: 98%
SOLUBILITY IN WATER: Slightly soluble
pH: Not applicable

SECTION IV ? FIRE & EXPLOSION HAZARDS

FLASH POINT: Tag Closed Cup 54 deg F (12.2 deg C)
IGNITION TEMPERATURE: 430 deg F
EXTINGUISHING MEDIA: Carbon dioxide, dry chemical, water mist, or fog.
SPECIAL FIREFIGHTING PROCEDURES: Do not use high pressure stream of water to extinguish burning material.
UNUSUAL FIRE & EXPLOSION HAZARD: Closed can exposed to flame and heat may erupt scattering burning fragments.

SECTION V ? REACTIVITY DATA

STABILITY:
Unstable:
Stable: X
CONDITIONS AND MATERIALS TO AVOID: Heat, open flame, strong oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS: None known.
HAZARDOUS POLYMERIZATION:
May occur:
Will not occur: X

SECTION VI ? HEALTH/HAZARD DATA

EYES: Can cause moderate irritation, redness, tearing.
SKIN: Prolonged or repeated contact can cause moderate irritation, defatting, dermatitis.
BREATHING: Excessive inhalation of vapors can cause nasal and respiratory irritation.
SWALLOWING: Can cause gastrointestinal irritation, nausea, vomiting, diarrhea.

SECTION VII ? EMERGENCY FIRST AID PROCEDURE

IF ON SKIN: Thoroughly wash exposed area with soap and water. Remove contaminated clothing. Launder contaminated clothing before re-use.
IF IN EYES: Flush with large amounts of water, lifting upper and lower lids occasionally. GET MEDICAL ATTENTION.
IF SWALLOWED: If victim in conscious, give two glasses of water, induce vomiting immediately by sticking finger down throat. Call a physician. Never give anything by mouth to an unconciuous person.
IF INHALED: Move individual to fresh air.

SECTION VIII ? OCCUPATIONAL EXPOSURE LIMITS

THRESHOLD LIMIT VALUE: Not established.

SECTION IX ? EMPLOYEE PROTECTION

RESPIRATORY PROTECTION: Not required under normal conditions of use.
VENTILATION: Not required under normal conditions of use.

SECTION X ? ENVIRONMENTAL PROTECTION

ENVIRONMENTAL PRECAUTIONS: Keep away from fire and other ignition sources. Avoid spills and leaking of this material. Absorb spilled material using paper, floor absorbents, or other absorbent material. Ventilate the area.

SECTION XI ? REGULATORY CONTROLS

DEPARTMENT OF TRANSPORTATION (DOT):
DOT CLASSIFICATION: ORM-D
DOT PROPER SHIPPING NAME: Consumer Commodity ORM-D
DOT EMERGENCY GUIDE NUMBER: Not applicable

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must conduct testing and/or make independent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees.

BLAZE PRODUCTS CORPORATION
Jelled Ethanol 8 oz. and 2 5/8 oz.
05/31/01

Blaze Products

JELLED ETHANOL (CONSUMER COMMODITY)

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES:
Although preparer and owner have taken reasonable
care in the preparation of this document, we
extend no warranties and make no representation
as to the accuracy or completeness of the information
contained herein, and assume no responsibility
regarding the suitability of this information for
the user's intended purposes or for the consequences
of its use. Each user should make a determination as
to the suitability of the information for their
particular purpose(s). This MSDS is the most recent
received from the product manufacturer or
distributor.

COMPAS Code: 47810060