

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard
 29 CFR 1910.1200. Standard must be
 consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

IDENTITY (As Used on Label and List)

Note: Blank spaces are not permitted. If any item is not applicable, or
 no information is available, the space must be marked to indicate that.

MARBROFIN X**Section I**

Supplied by INTERNATIONAL STONWORKS, INC.	Emergency Telephone Number (713) 654 -1701
Address (Number, Street, City, State, and Zip Code) 2523 Fairway Park, Ste 510, Houston, TX 77092	Telephone Number for Information (713) 956 - 8291 Website Address www.intlstoneworks.com
	Date Prepared January 1, 2002
	Signature of Preparer (optional)

Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity: Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits	%(optional)
Oxalic Acid				35- 45%
Magnesium Hexafluorosilicate 6				5 - 10%

Section III - Physical/Chemical Characteristics

Boiling Point	N/A	Specific Gravity (H ₂ O = 1)	1 gr/cm³
Vapor Pressure (mm Hg.)	N/A	Melting Point	N/A
Vapor Density (AIR =1)	N/A	Evaporation Rate (Butyl Acetate = 1)	N/A
Solubility in Water	PARTIAL	Ph	(wet) 3

Appearance and Odor

Green Powder / None**Section IV - Fire and Explosion Hazard Data**

Flash Point (Method Used)	N/A	Flammable Limits	LEL	UEL
			N/A	
Extinguishing Media	N/A			
Special Fire Fighting Procedures	N/A			
Unusual Fire and Explosion Hazards	N/A			

OSHA 174, Sept. 1985

MARBROFIN X

